

HYRAX 2T FB MOTORCYCLE OIL

DESCRIPTION

HYRAX 2T FB MOTORCYCLE OIL is recommended for air-cooled, two-cycle engines in all applications which do not specify NMMA TCW II or TCW III. It is specifically formulated with a unique combination of detergents and ash free dispersants for high temperature two-cycle, air-cooled engines of the most modern motorcycles, scooters and mopeds equipped with oil injection system as well as petrol mixtures.

APPLICATION

Recommended for air-cooled two stroke engines in all application except for outboard engines.

BENEFITS

- High temperature protection
- Protects against deposits and ring sticking
- Ideal for air-cooled two-cycle engines
- Suitable for pre-mix or injector system
- Pre-diluted for easier gasoline mixing

PERFORMANCE

- API TSC-3/TC
- JASO FB



TYPICAL PROPERTIES

PROPERTIES	METHOD	TYPICAL RESULTS
Density at 15°C, g/cm ³	ASTM D 4052	0.8677
Viscosity cSt	ASTM D 445	
at 40°C,		59.61
at 100°C		8.2
Viscosity Index	ASTM D 2270	106
Colour		Green

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.