

HYRAX COMPRO

DESCRIPTION

HYRAX COMPRO is designed for the lubrication of air compressors (rotary and reciprocating types). It is blended from selected highly refined mineral oils, with naphthenic-paraffinic structure and treated with anti-oxidant, anti-rust and anti-wear additives.

APPLICATION

Recommended for rotary screw and reciprocating compressors operating under normal to severe conditions.

BENEFITS

- The chemical composition of the oils provide neutral detergent characteristic
- Low pour point
- Low volatility
- Excellent demulsibility (rapid water separation)
- Good natural chemical stability

PERFORMANCE

- DIN 51506 FOR VDL OILS
- MIL-L-26087



TYPICAL PROPERTIES

PROPERTIES	METHOD	ISO VG 32	ISO VG 68	ISO VG 100	ISO VG150
Density at 15°C g/cm ³	ASTM D 4045	0.870	0.875	0.880	0.901
Flash Point, °C (C.O.C)	ASTM D 92	196	208	218	230
Viscosity	ASTM D 445				
at 40°C, cSt		33.3	66.8	92	159
at 100°C, cSt		5.20	8.04	9.8	14.0
Viscosity Index	ASTM D 2270	83	85	83	82
Acid Number mgKOH/g	ASTM D 664	0.04	0.04	0.04	0.04

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.