

PASSENGER CAR MOTOR OIL

HYRAX CARINA

DESCRIPTION

HYRAX CARINA SAE 20W/50 is a high performance multigrade motor oil formulated from a selected high quality mineral base oils and unique additive technology for use in passenger cars and light truck gasoline or diesel engines. It also provides superior fuel efficiency and engine protection under all conditions.

APPLICATION

Recommended for high performance turbocharged, supercharged gasoline and diesel multi-valve fuel injected engines operating under high speed to severe service associated with stop and go driving.

BENEFITS

- Longer oil drain interval
- Outstanding thermal and oxidation stability
- Excellent detergency property to prevent deposit deposits and sludge build-up
- Improved power output
- Improved fuel economy

PERFORMANCE

- API SM/CG-4
- ACEA A3/B3
- MB 229.3, 229.1
- VW 505 00



TYPICAL PROPERTIES

PROPERTIES	METHOD	SAE 10W/30	SAE 15W/40	SAE 20W/50
Density at 15°C, g/cm ³	ASTM D 4052	0.8510	0.8881	0.888
Flash Point, °C (C.O.C)	ASTM D 92	>210	>210	>210
Viscosity, cSt	ASTM D 445			
at 40°C		75.8	90.2	174
at 100°C		11.0	14.6	19.1
Viscosity Index	ASTM 2270	135	135	125
Total Base No., mgKOH/g	ASTM D 2896	7.0	7.0	7.0
Color	ASTM D 1500	2.0	2.0	2.0

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.