

HYRAX ULTRA

DESCRIPTION

HYRAX ULTRA is a high quality multigrade lubricant recommended for passenger cars and commercial vehicles. It is formulated from selected base oils and special additives which provide oxidation stability and high degree of detergent and dispersant characteristics.

APPLICATION

Recommended for supercharged or naturally aspirated gasoline and diesel engines in passenger cars and commercial vehicles requiring the manufacturer's recommendation of API service category SF/CC. It can also be used where API SE/CC and lower API level oils are recommended.

BENEFITS

- For all year round use
- Excellent shear stability
- Minimises deposit formations at high temperature operation
- Protects against rust, wear and sludge formation

PERFORMANCE

- API SF/CC
- DAIMLER BENZ 226.1
- MIL-L-46152C
- MIL-L-2104B
- CCMC G2/D1



TYPICAL PROPERTIES

PROPERTIES	METHOD	SAE 15W/40	SAE 20W/50
Density at 15 ^o C, g/cm ³	ASTM D 4052	0.8690	0.8733
Flash Point, ^o C (C.O.C)	ASTM D 92	>210	>210
Viscosity, cSt	ASTM D 445		
at 40 ^o C		107.1	159.1
at 100 ^o C		14.2	18
Viscosity Index	ASTM D 2270	135	125
Total Base No., mgKOH/g	ASTM D 2896	5	5
Colour	ASTM D 1500	L 2.0	L 2.0

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.